

Clear Coat

Art.: 02.3132.6100
Aerosol can 500 ml

Clear Coat is a very high-quality and crystal clear finish in a spray can with properties that equal those of a professional spray-gun. It is a quick-drying lacquer with good filling properties. After drying, it provides a scratch and wear resistant coating of OEM quality that is perfectly UV resistant. Clear Coat gives the treated surface a perfect and long-lasting shine.



Base:	Pure acrylic resin
Density:	792 kg/m ³
Consistency:	Liquid (ready-to-use in aerosol)
Flash point:	< 0°C
Temperature resistance:	Up to 120°C
UV resistance:	Excellent (does not yellow)
Solvent resistance:	Good, in the case of brief contact and after full cure
Application conditions:	+15°C to +30°C
Type of surface:	Almost all matted old paint layers, both conventional and water-based base coats, metal, non-ferrous metal and most plastics
Surface preparation:	The surface must be clean, dry and free of dust and grease. Clean the surface with Innotec Multisol . Clean plastic surfaces with Innotec Repaplast Cleaner Antistatic , then pre-treat them with Innotec Repaplast Primer New Formula .
Application method:	Shake can well during 2 minutes before use. Spraying distance 25-30 cm. First apply 1 thin layer, then 2 smooth criss-cross layers. Leave 5 minutes for the product to evaporate between two layers. After use, invert can and spray until clear to clean the nozzle.
Dust dry:	After ± 5 to 10 minutes (at 20°C / 65% relative humidity)
Curing time:	After 2 hours at 20°C / 65% relative humidity and depending on the layer thickness
Recommended layer thickness:	First 1 thin layer, then 2 smooth criss-cross layers
Sandability:	Excellent after ± 1 hour
Paintability:	After full curing. Test beforehand on a non-visible area.
Cleaning of materials used:	With Innotec Multisol
Cleaning of hands:	With Innotec Power Scrubs or with Innotec Safe Hand Clean Plus and water
Shelf life:	2 years in original, unopened packaging
Type of batchcode:	F





Other details: The unique nozzle-riser combination enables the same quality result as achieved from a professional gravity feed gun.

EAN Code: 5400563011102

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

