

TECHNICAL INFO

Clear Mount Tape 12 mm

Art.: 05.2324.6100 Roll 10 m

Clear Mount Tape is a universally applicable double-sided transparent adhesive tape which is made from 100% acryl by a unique production process. This means that it combines an extremely strong core with outstanding adhesive power.



Base:	Acryl tape
Density:	1025 kg/m³
Dimensions:	12 mm x 0,5 mm x 10 m
Hardness:	72 (Shore A)
Tensile strength:	0,90 N/mm² (according to ASTM D-3654)
Elongation at break (%):	900% (according to ASTM D-412)
Shear strength:	0,41 N/mm² (according to ASTM D-3654)
Peel strength:	35 N/cm (90° after 1 hour / at 23°C) 58 N/cm (90° after 1 hour / at 70°C)
Temperature resistance:	-35°C to +95°C
Peak temperature resistance:	+120°C
Water resistance:	Excellent
Solvent resistance:	Moderate
Application conditions:	+15°C to +50°C
Type of surface:	On almost every (transparent) smooth surface
Surface preparation:	The surface must be clean, dry and free of grease. Clean surfaces with Innotec Multisol or Innotec Seal and Bond Remover.
Application method:	Apply straight from the roll and press firmly. Remove protective film and join both parts carefully. Parts can be repositioned within 5 minutes. When the parts are correctly aligned press firmly to activate the pressure sensitive glue layer. Maximum adhesion after 24 hours.
Correction time:	Very short
Cleaning of hands:	With Innotec Power Scrubs or with Innotec Safe Hand Clean Plus and water
Shelf life:	1 year in original, unopened packaging
Storage conditions:	Store cool and dry, at a temperature between +5°C and 20°C
Type of batchcode:	F







EAN Code:

5400563026687

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.



