

## Easy Gasket 275 ml

Art.: 01.1407.0000

275 ml

Easy Gasket is a very high-grade and easy-to-use gasket maker, to replace or support all standard gaskets or seals in cars, trucks, boats, motorcycles, ... e.g. for the gearbox, drive shafts, crankshafts, sump, and dynamo, ignition or clutch cover.



Base:	Synthetic rubber
Density:	1040 kg/m <sup>3</sup>
Consistency:	Pasty
Solvents:	No solvents
Hardness:	± 17 (Shore A)
Tensile strength:	± 1,70 N/mm <sup>2</sup>
Elongation at break (%):	± 380%
Modulus:	± 0,35 N/mm <sup>2</sup> (at 100% elongation)
Temperature resistance:	-50°C to +200°C
Peak temperature resistance:	270°C
UV resistance:	Very good
Water resistance:	Very good
Solvent resistance:	Good
Acid resistance:	Good
Slump resistance (constancy):	Very good
Application conditions:	+5°C to +40°C
Type of surface:	Metal, glass, paper, cork, aluminium, rubber and most plastics
Surface preparation:	The surface must be clean, dry and free of grease. Clean surfaces with Innotec <a href="#">Multisol</a> or Innotec <a href="#">Power Clean</a> .
Application method:	Apply evenly straight from the packaging to one of the parts to be glued. Press parts together within 5 minutes. Turn finger-tight. Tighten after 20 minutes on the prescribed tightening moment.
Open time:	5 minutes
Skin formation:	6 minutes (23°C / 50% relative humidity)





Tack free:	8 minutes
Curing time:	± 2 mm in 24 hours
Maximum admissible deformation:	25%
Cleaning of materials used:	With Innotec <a href="#">Multisol</a>
Cleaning of hands:	With Innotec <a href="#">Power Scrubs</a> or with Innotec <a href="#">Safe Hand Clean Plus</a> and water
Shelf life:	1 year in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F
Other details:	Not suitable for applications where this product will be immersed in petrol. OEM approved
EAN Code:	5400563001943

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

