

Easy Seal XS 310 ml White

Art.: 01.1453.0100

310 ml

Easy Seal XS is a unique plasticizer-free joint sealant that retains its elasticity. Therefore, it is very well suited for bathroom materials, natural stone, etc. The product is low-odour and free of solvents and MEKO which makes it safe to use even on very sensitive surfaces. Easy Seal XS has good adhesion to various surfaces like natural stone, concrete, ceramic tiles, glazed tiles, mirrors, glass, wood, metals and many plastics.



Base:	Alcoxy
Density:	± 1010 kg/m ³
Consistency:	Pasty
Solvents:	No solvents
Hardness:	± 25 (Shore A)
Tensile strength:	± 0,52 N/mm ² (according to DIN 53504)
Elongation at break (%):	± 215% (according to DIN 53504)
Modulus:	± 0,36 N/mm ² (at 100% elongation) (according to DIN 53504)
Shear strength:	0,6 N/mm ² (according to DIN 53283)
Elastic recovery:	± 100%
Temperature resistance:	-40°C to +150°C
UV resistance:	Very good
Water resistance:	Very good
Solvent resistance:	Good, resistant against different solvents
Fungus resistance:	Very good
Slump resistance (constancy):	Good
Tests:	Registered by NSF (class R2), register number: 143799
Application conditions:	+5°C to +30°C
Type of surface:	The most common building materials such as natural stone, concrete, ceramic and glazed tiles, mirrors, glass, wood, metals and many plastics
Surface preparation:	The surface must be clean, dry and free of grease. Clean surfaces with Innotec Multisol or Innotec Seal and Bond Remover . Plastic, porous or extremely difficult surfaces must be pre-treated with Innotec Replast Primer New Formula ou Innotec Seal Guard .
Application method:	Apply Easy Seal XS directly from the cartridge using a glue gun (InnoQuip Pro 2000 Gun , Easy Grip Gun or Air Sealant Applicator 300). If necessary smooth with Innotec Seal Fluid .





If applied in pools/basins:	Make sure the surface is clean, dry and free of grease. Always use a suitable primer (e.g. Innotec Seal Guard). Use Innotec Back Fill Foam to dimension the joint exactly and/or to prevent three point attachment. Advice: max seam depth = (width/3) + 6 mm. Easy Seal XS should only be immersed after thorough drying.
Skin formation:	After ± 10 minutes (at 23°C / 50% relative humidity)
Tack free:	After 60 minutes (at 23°C / 50% relative humidity)
Curing time:	± 2 mm in 24 hours (at 23°C / 50% relative humidity)
Minimum joint width:	4 mm
Maximum joint width:	20 mm
Maximum admissible deformation:	20%
Paintability:	Not paintable
Cleaning of materials used:	With Innotec Multisol
Cleaning of hands:	With Innotec Power Scrubs or with Innotec Safe Hand Clean Plus and water
Shelf life:	1 year in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F
Other details:	Smoothing with Seal Fluid on natural stone can cause discolouring as a cause of the Seal Fluid. As a result of the continuously changing water quality in pools and bassins, the lifetime of Easy Seal XS cannot be defined univocally if the product is applied in pools/basins. OEM approved
CE Certification:	Easy Seal XS is a product with CE mark in accordance with Regulation (EU) 305/2011: CE EN 15651-1:2012, F INT-EXT 20LM CE EN 15651-3:2012, XS1
EAN Code:	5400563002490

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

