

TECHNICAL INFO

Fuel Plus

Art.: 04.0168.9999

Bottle 250 ml

Fuel Plus is a highly effective additive for maintaining the entire fuel system of petrol engines, including E85 (bioethanol). The product optimises combustion, which results in less pollution and wear.



Still fluid at:	< -30°C
Base:	Selected petroleum derivates with special additives
Density:	810 kg/m ³
Consistency:	Liquid
Flash point:	72°C
Tests:	Improving test with polluted carburettor: (Renault 5 Test) Scale: clean = 10,0 0.000 ppm added = 1,0 1.000 ppm added = 9,2
Application conditions:	No restriction
Application method:	Shake the bottle before use. Add Fuel Plus to the fuel tank before filling. For best results repeat every 5000 - 10000 km. Fuel Plus can be combined with Valve Clean and Injection Clean .
Cleaning of hands:	With Innotec Power Scrubs or with Innotec Safe Hand Clean Plus and water
Shelf life:	5 years in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F
EAN Code:	5400563019573

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.





For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

