

Hi-Temp Wax Spray Black

Art.: 02.2118.0000
Aerosol can 500 ml

Hi-Temp Wax Spray is a very durable underbody & cavity coating based on saponified fatty acids and also an excellent rust protection for sheet metal parts and cavities in OEM quality. It has an excellent penetration and water-repellent power which enables it to soak into the smallest gaps and thus reliably protect the surface for a long time.

Due to its special chemical composition Hi-Temp Wax has an extremely high temperature resistance. The product remains absolutely stable up to a temperature of 150°C. Due to its very high temperature resistance Hi-Temp Wax is extremely well suited for use in the engine compartment of the vehicle and in engine rooms - the product will not run off.

Hi-Temp Wax can be used to protect metal and sheet metal against corrosion during construction or repairs. The product is mostly applied to the inside of doors, chassis parts, beams, etc.

Hi-Temp Wax can also be applied with effect to protect power points, battery poles and other electrical components subject to the effects of weather, dampness, dirt and salt. Hi-Temp Wax ensures that these parts are highly water-repellent, as a result of which faults due to permeating dampness or corrosion can be kept to a minimum.

Hi-Temp Wax is available in two types of packaging: in an aerosol can and in a 1 litre can.

The 1 litre can is very economical and perfectly sprayable with the InnoQuip [Pressure Pot Gun](#). The wide range of settings available on this gun allows you to spray layers of any thickness. For optimal treatment of cavities use the [Cavity Tube Set](#).

The aerosol can is extremely user-friendly and easy to apply. When being applied the product initially is liquid, so it can penetrate deeply between the parts. After the propellant has evaporated away it leaves a beautiful, solid and pressure-resistant grease behind. The extra nozzle and tube supplied with the product make it very easy to apply in places which are difficult to access. For optimal treatment of cavities use the [Hi-Temp Wax Spray Tube](#).

- Insensitive to many chemicals (brake fluid, salt, etc.).
- Excellent flow properties, but no long-term seepage after application.
- Easy processing - no dismantling or covering of rubber and plastic parts needed.
- High temperature resistance (up to 150°C).
- Aromatic and silicone free, with a neutral odour.
- Perfect rust protection.

