

Solid Spray Filler

Art.: 02.1200.9999

Aerosol can 500 ml

Solid Spray Filler is a high-quality fine spray filler with a very high solid content. Thanks to its special composition, this product has an unprecedentedly high filling power and outstanding sandability.



Base:	Pure acrylate
Density:	980 kg/m ³
Consistency:	Liquid (ready-to-use in aerosol)
Solvents:	Mixture of aromatic and aliphatic solvents
Flash point:	< 0°C
Temperature resistance:	-20°C to +110°C
Solvent resistance:	Moderate
Application conditions:	+15°C to +30°C
Type of surface:	Sanded layers of old paint, metal, all non-ferrous metals, aluminium, wood, MDF, galvanized metal, plaster and most common plastics
Surface preparation:	The surface must be clean, dry and free of dust and grease. Sand the surface. Clean surfaces with Innotec Multisol . Clean plastic surfaces with Innotec Repaplast Cleaner Antistatic and pre-treat with Innotec Repaplast Primer New Formula .
Application method:	Shake can well during at least 2 minutes before use. Spraying distance 20 cm. Apply in several thin layers. When applying several layers leave 5 minutes between each layer for the product to evaporate. After use invert can and spray until clear to clean the nozzle.
Dust dry:	After ± 10 minutes (at 20°C)
Curing time:	60 minutes (at 20°C / 65% relative humidity / 30µ layer thickness)
Recommended layer thickness:	30µ
Sandability:	After ± 25 minutes (at 20°C)
Paintability:	After ± 25 minutes (at 20°C) Solid Spray Filler is compatible with almost all modern groundcoat systems. Due to the huge variety of paint types on the market, it is best to test the paint beforehand. Always seal with a base layer.
Cleaning of materials used:	With Innotec Multisol
Cleaning of hands:	With Innotec Power Scrubs or with Innotec Safe Hand Clean Plus and water
Shelf life:	2 years in original, unopened packaging





Storage conditions: Store cool and dry

Type of batchcode: F

EAN Code: 5400563008522

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

