

Thread Seal

Art.: 01.0608.0555

2 chamber pressure can 100 ml

Thread Seal is a many-sided thixotropic thread sealer with PTFE for connections of compressed air and liquid transport pipes. Suitable for almost any type of screw thread.

Thread Seal is the perfect solution for the quick and professional sealing of threaded connections, thereby allowing later dismantling. The product not only creates a reliable seal, it also protects the thread surface against corrosion, as a result of which later dismantling can be performed quickly, easily and without causing damage.

This thread sealing product based on methacrylate compounds with PTFE additives cures very quickly by anaerobic reaction in the presence of metal acting as a catalyst. Therefore, it is capable of carrying loads almost immediately after mounting (hermetic seal).

In its unique packaging Thread Seal is not only user-friendly, but also easy to apply and to dose with precision. The product is perfectly locked up in its can preventing it from being contaminated, as a result of which quality remains optimal.

- Gel-based thread sealer.
- Unique packaging allowing precise dosing.
- Universally applicable thanks to certifications such as DIN EN 751-1, WRAS (register no. 1810561) and NSF (register no. 146033).
- Optimal shelf-life.
- Only 1 product for almost all types of fine and coarse threads.
- Cost-reducing; often removes the need for PTFE tape, flax, hamp.
- Can be used for threaded connections between metals, plastics and ceramics, provided that 1 of the products is a metal (catalyst).
- Easy to use in all positions (also upside down).
- Protects against corrosion.
- Reliable connection without using additional primers or activators.

