

Versabond 310 ml Black

Art.: 01.2416.0000

310 ml

Versabond is a unique construction adhesive with lasting elasticity based on the latest SPUR polymer techniques. The product is very suitable for bonding and sealing nearly all surfaces in the automotive and construction sector such as metal, aluminium, concrete, stone, wood, construction foil, PVC, EPDM, rubber, pond liner, ferrous and non-ferrous metals.



Base:	SPUR Polymers
Density:	± 1235 kg/m ³
Consistency:	Pasty
Solvents:	No solvents
Temperature resistance:	-35°C to +90°C
Water resistance:	Very good
Slump resistance (constancy):	Reasonable, flows after
Percentage of solids:	100%
Shrinkage:	No shrinkage
Application conditions:	+5°C to +35°C
Type of surface:	Different building and construction materials such as concrete, stone, wood, construction foil, PVC, EPDM, pond liner, ferrous and non-ferrous metals
Surface preparation:	The surface must be clean, dry and free of grease. Clean surfaces with Innotec Multisol or Innotec Seal and Bond Remover . Clean plastic surfaces with Innotec Repaplast Cleaner Antistatic .
Application method:	Apply directly from the cartridge using a glue gun (InnoQuip Pro 2000 Gun , Easy Grip Gun or Air Sealant Applicator 300). When gluing, join the parts together within 5 minutes. When leaving the parts lie open for max. 1 hour before assembly, a stronger starting adhesion will be achieved.
Skin formation:	None. The product remains sticky to a certain degree.
Curing time:	Completely after ± 2 days
Paintability:	Not paintable
Cleaning of materials used:	With Innotec Multisol
Cleaning of hands:	With Innotec Power Scrubs or with Innotec Safe Hand Clean Plus and water
Shelf life:	1 year in original, unopened packaging
Storage conditions:	Store cool and dry





Type of batchcode:	F
Other details:	There will be permanent deformation under heavy tensile or shear load.
EAN Code:	5400563003527

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

