

## Antislip Spray

Art.: 02.1440.6100  
Aerosol can 500 ml

Antislip Spray is a fine-grained transparent 1K coating to make smooth surfaces non-slip. This coating provides high slip resistance on various walkable surfaces, such as stairs, steps, landings and footboards, but is also suitable for ladders, handles, shower/bath/pool surrounds and floors in changing rooms. Thanks to the use of pure acrylic resin combined with polyethylene particles, the product after application forms a clear, wear-resistant, and UV-resistant layer that is also highly resistant to weather influences.



When applied in accordance with the instructions, Innotec Antislip Spray forms a coating with slip resistance values that meet the highest safety requirements for walkable surfaces.

Thanks to the aerosol packaging, Antislip Spray is extremely easy to apply, even on round or curved surfaces. Antislip Spray has excellent adhesion to most common surfaces such as concrete, natural stone, tiles, wood, hard plastics, stainless steel and coated (metal) surfaces. The product must be applied on a clean, dry, dust and grease free surface, that has been roughened with an abrasive fleece and cleaned with Innotec [Multisol](#). Plastic surfaces should be cleaned with Innotec [Repaplast Cleaner Antistatic](#) and pre-treated with Innotec [Repaplast Primer New Formula](#). To improve adhesion on porous surfaces, it is advisable to pretreat them with Innotec [Seal Guard](#). Pre-treat bare metal with Innotec [Construction Primer](#).

- Dust dry after 20 minutes, capable of carrying loads after 24 hours.
- For indoor and outdoor applications.
- Suitable for sanitary applications.
- Transparent.
- Wear-resistant and high slip resistance (R13 according to DIN 51130).
- Suitable for frequent water exposure.

