

Hi-Temp Wax Dry 1 l Transparent

Art.: 02.2424.6100

1 l

Hi-Temp Wax Dry is a very durable and tack-free wax coating based on microcrystalline waxes that offers excellent rust protection in factory original quality for sheet metal parts, cavities and (machine) parts. It has an excellent penetration and water-repellent power which enables it to penetrate into the smallest gaps and thus reliably protect the surface for a long time. Thanks to the addition of a UV indicator, the presence of Hi-Temp Wax Dry can always be checked.



Base:	Microcrystalline waxes and sulfonates
Density:	885 kg/m ³ at 20°C
Consistency:	Liquid
Solvents:	Aliphatic hydrocarbons
Flash point:	65°C (according to DIN 53213)
Temperature resistance:	-40°C to +170°C
Water resistance:	Excellent
Solvent resistance:	Good
Tests:	Salt spray test (according to ISO 9227): excellent after 4000 hours, Ri 0 at 100µ dry layer
Application conditions:	+15°C to +35°C
Type of surface:	Ferrous and non-ferrous metals
Surface preparation:	The surface must be clean, dry and free of grease. Clean surfaces with Innotec Multisol or Innotec Seal and Bond Remover .
Application method:	Shake well before use. Spray with a traditional screw-on gun such as the Innotec Pressure Gun Basic (4-6 bar) or by means of the Pressure Pot Gun specially developed for this purpose (2-4 bar, possibly in combination with the special Cavity Tube Set for hollow spaces). Can also be sprayed using the Multi Sprayer 1,3 l . Spraying distance 25-30 cm. Apply in an even, closed layer.
Tack free:	After ± 3 days (100µ layer thickness (wet) / at 20°C / 65% relative humidity and with adequate ventilation)
Dust dry:	After ± 24 hours (100µ layer thickness (wet) / at 20°C / 65% relative humidity and with adequate ventilation)
Recommended layer thickness:	300µ to 350µ wet (dense layer)
Paintability:	Not paintable
Cleaning of materials used:	With Innotec Multisol
Cleaning of hands:	With Innotec Power Scrubs or with Innotec Safe Hand Clean Plus and water





Shelf life: 1 year in original, unopened packaging

Storage conditions: Store cool and dry

Type of batchcode: F

Other details: Contains UV indicator

EAN Code: 5400563036655

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

