

## TECHNICAL INFO

### Versa Tape 5 mm

Art.: 01.1342.0000

Roll 20 m

Versa Tape is a very easy-to-use sealant on a roll. Versa Tape can be used for fast and simple, but long-lasting sealing jobs.



Base:	Butyl
Density:	1100 kg/m <sup>3</sup>
Dimensions:	5 mm x 20 m
Hardness:	60-70 (Shore 00)
Tensile strength:	± 0,15 N/mm <sup>2</sup>
Elongation at break (%):	300%
Shear strength:	± 0,21 N/mm <sup>2</sup>
Peel strength:	± 0,2 N/mm <sup>2</sup>
Compressibility:	0,05 N/mm <sup>2</sup> (20%)
Temperature resistance:	-40°C to +90°C
Water resistance:	Good
Saltwater resistance:	Good
Solvent resistance:	Not resistant to solvents
Acid resistance:	Very good
Tests:	Cold shock resistant to -40°C
Application conditions:	0°C to +40°C
Type of surface:	The most common materials such as metal, aluminium, glass, wood, concrete and plastics
Surface preparation:	The surface must be clean, dry and free of grease. Clean surfaces with Innotec <a href="#">Multisol</a> or Innotec <a href="#">Seal and Bond Remover</a> . Clean plastic surfaces with Innotec <a href="#">Repaplast Cleaner Antistatic</a> .
Application method:	<u>When gluing:</u> Cut off the required length and apply to the surface. Align both sides and press firmly together. <u>When sealing:</u> Cut off the required length, apply in and around the seal, and press firmly.





Cleaning of materials used:	With Innotec <a href="#">Multisol</a>
Cleaning of hands:	With Innotec <a href="#">Power Scrubs</a> or with Innotec <a href="#">Safe Hand Clean Plus</a> and water
Shelf life:	2 years in original, unopened packaging
Storage conditions:	Store cool and dry, at a temperature between +5°C and 20°C
Type of batchcode:	F
EAN Code:	5400563001639

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

